

(DM) Dura Mate™AHDM/AHDBM ISOBUS 91 Series

Environmentally-Sealed, Multi-Pin, Heavy-Duty, Metal Circular ISOBUS Connectors

Available in Size 24, 9 Position

Amphenol Sine Systems' **DuraMate™ AHDM/AHDBM ISOBUS 91 Series** of environmentally-sealed, multi-pin, heavy-duty, circular metal plugs (AHDM) and breakaway metal (AHDBM) plugs & receptacles provide an economical, quick-connect, bayonet locking system **designed to meet ISO 11783 standards (for control and communications between tractors, implements and software) and withstand the challenges and complexities of harsh environment, off-road, agricultural applications.**



AHDBM Circular Bayonet Breakaway-Ready Receptacle

AHDM Circular Bayonet Standard Plug

AHDBM Circular Bayonet Breakaway Plug

Key ISOBUS 91 Series Features

- + One-to-one alternative for all HD30/HDB36 parts
- Compatible to other industry standard (Circular Bayonet) versions while retaining full breakaway functionality
- + AHDM 91 Series Plugs have a jumper (bridged contacts) between Pin 4 & 5
- + AHDM/AHDBM 91 Series Receptacles don't have a jumper (bridged contact)
- Options for up to 16mm² power wires
- Full range of backshell options

Contact Legend (Size/Max. Current)			
• •		•	•
8/ 60A 6AWG	8/ 60A 8-10AWG	12/ 25A	16/ 13A





Important

- AHDBM 91 Series Plugs are intermateable to other industry standard versions and allow full breakaway functionality if used with suitable breakaway-ready Receptacles (like AHDBM 91 Receptacles)
- AHDM 91 Series Plugs are intermateable to other industry standard versions but do not retain breakaway functionality
- AHDBM 91 Series Receptacles (Circular Bayonet) are intermateable to other industry standard plugs and allow breakaway functionality when
 used with a breakaway Plugs (like AHDBM 91 Plugs)
- Available upon request and not shown on this flyer: AHDM 91 Series Receptacles (Drop Shaped Bayonet) are not intermateable to all industry standard versions and do not retain breakaway functionality

DuraMate™ Features

- 3 key-way bayonet design ensures proper mating of connectors
- High density signal and mixed power insert configurations
- Operating temperature range: -55°C to +125°C
- High-strength, impact resistant & lightweight zinc-alloy metal housings
- Low-insertion force stamped terminals offer improved manufacturing efficiencies
- Standard Wide Thread Adapters provide maximum access to rear grommet and improved serviceability with a wide variety of backshell options
- Environmentally-sealed and engineered rapid and secure mating system achieves IP67/IP69K protection (in mated condition) from ingress of dust, water, mud and other contaminants and is vibration resistent
- Sealing features consisting of durable high-temperature silicone provide barrier from lubricating oils, hydraulic fluids and fossil fuels
- Backshells maintain a compression-fit design to resist maximum pull-out forces and facilitate strain-relief for jacketed cable ranges
- Utilizes A Series[™] standard contact system (Stamped & Formed or Machined)
- Wire entry sealing available in four separate ranges for discrete wire applications

















Standard products. Custom solutions
Customer Service +1 800 394 7732

DuraMate[™] AHDM/AHDBM ISOBUS 91 Series - Material & Performance Specifications

Current Rating per Contact Size 8, 60A; Size 12, 25A; Size 16, 13A		Housing Material	Zinc-alloy/Aluminum-alloy
Operating Temperature	-55°C to +125°C	Insulation Insert	Thermoplastic
Dielectric Withstanding Voltage	Current Leakage-2mA at 1500 VAC	Seal	Silicone Rubber
Degree of Protection	IP67/69K (in mated condition)	Contact	A Series™ Common System
Mating Cycle Durability	100 Cycles	Compliance	RoHS

DuraMate™ AHDM/AHDBM ISOBUS 91 Series - Recommended Wire Insulation Overall Diameter (OD)

Contact Size	Typical Wire Range	Normal Seal	Reduced Seal	Reduced Seal for 6AWG/16mm² (Size 8 Contacts Only)
8	6-10AWG (5.0-16.0mm²)	4.83-6.10mm (0.190-0.240")	3.43-5.59mm (0.135-0.220")	6.50-7.42mm (0.256-0.292")
12	10-14AWG (6.0 2.0mm²)	3.40-4.32mm (0.134-0.170'')	2.46-4.01mm (0.135-0.158")	2.46-4.01mm (0.135-0.158")
16	14-20AWG (2.0-0.5mm²)	2.54-3.40mm (0.100-0.134")	1.35-3.05mm (0.053-0.120")	1.35-3.05mm (0.053-0.120")

DuraMate™ AHDM/AHDBM ISOBUS 91 Series - Backshell Options and Accessory Overview



Contact Removal Tools

DuraMate™ AHDM ISOBUS 91 Series -Standard Plug (mm)

DuraMate™ AHDBM ISOBUS 91 Series -Breakaway Plug (mm)

DuraMate™ AHDBM ISOBUS 91 Series -Breakaway-Ready Receptacle (mm)







Wide Thread Adapter

DuraMate™ AHDM ISOBUS 91 Series - Standard Plugs

lmage	Part Number	Description	Amps	Voltage
	AHDM06-24-91SN	Size 24, 9 Pos, Plug, Socket, DuraMate™ AHDM ISOBUS 91 Series, Metal, Normal Seal, Wide Thread Adapter	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDM06-24-91SN-059	Size 24, 9 Pos, Kit, Plug, Socket, DuraMate™ AHDM ISOBUS 91 Series, Metal, Normal Seal, Wide Thread Adapter, Cable Clamp Backshell	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDM06-24-91SR	Size 24, 9 Pos, Plug, Socket, DuraMate™ AHDM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDM06-24-91SR-059	Size 24, 9 Pos, Kit, Plug, Socket, DuraMate™ AHDM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Cable Clamp Backshell	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDM06-24-91SR16	Size 24, 9 Pos, Plug, Socket, DuraMate™ AHDM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Size 8 Contact, 6AWG/16mm² Wire Seal Note: Use AT62-203-08141-16 contacts for 6AWG/16mm² applications	Size 8, 6AWG, 60A Size 12, 25A Size 16, 13A	250V
	AHDM06-24-91SR16-059	Size 24, 9 Pos, Kit, Plug, Socket, DuraMate™ AHDM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Cable Clamp Backshell, Size 8 Contact, 6AWG/16mm² Wire Seal Note: Use AT62-203-08141-16 contacts for 6AWG/16mm² applications	Size 8, 6AWG, 60A Size 12, 25A Size 16, 13A	250V

DuraMate[™] AHDBM ISOBUS 91 Series - Breakaway Plugs

lmage	Part Number	Description	Amps	Voltage
	AHDBM06-24-91SN	Size 24, 9 Pos, Plug, Socket, DuraMate TM AHDBM ISOBUS 91 Series, Metal, Normal Seal, Wide Thread Adapter, Breakaway	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM06-24-91\$N-059	Size 24, 9 Pos, Kit, Plug, Socket, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Normal Seal, Wide Thread Adapter, Cable Clamp Backshell, Breakaway	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM06-24-91SR	Size 24, 9 Pos, Plug, Socket, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Breakaway	Size 8, 60A Size 12, 25A Size 16, 13A	250V

DuraMate™ AHDBM ISOBUS 91 Series - Breakaway Plugs, cont.

Image	Part Number	Description	Amps	Voltage
	AHDBM06-24-91SR-059	Size 24, 9 Pos, Kit, Plug, Socket, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Cable Clamp Backshell, Breakaway	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM06-24-91SR16	Size 24, 9 Pos, Kit, Plug, Socket, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Cable Clamp Backshell, Breakaway, Size 8 Contact, 6AWG/16mm² Wire Seal Note: Use AT62-203-08141-16 contacts for 6AWG/16mm² applications	Size 8, 6AWG, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM06-24-91SR16-059	Size 24, 9 Pos, Plug, Socket, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Breakaway, Size 8 Contact, 6AWG/16mm² Wire Seal Note: Use AT62-203-08141-16 contacts for 6AWG/16mm² applications	Size 8, 6AWG, 60A Size 12, 25A Size 16, 13A	250V

DuraMate[™] AHDBM ISOBUS 91 Series - Breakway-Ready Receptacles

lmage	Part Number	Description	Amps	Voltage
	AHDBM04-24-91PN	Size 24, 9 Pos, Receptacle, Pin, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Normal Seal, Wide Thread Adapter, Breakway-Ready	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM04-24-91PN-059	Size 24, 9 Pos, Kit, Receptacle, Pin, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Normal Seal, Wide Thread Adapter, Cable Clamp Backshell, Breakway-Ready	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM04-24-91PR	Size 24, 9 Pos, Receptacle, Pin, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Breakway-Ready	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM04-24-91PR-059	Size 24, 9 Pos, Kit, Receptacle, Pin, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Cable Clamp Backshell, Breakway-Ready	Size 8, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM04-24-91PR16	Size 24, 9 Pos, Receptacle, Pin, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Breakway-Ready, Size 8 Contact, 6AWG/16mm² Wire Seal Note: Use AT60-204-08141-16 contacts for 6AWG/16mm² applications	Size 8, 6AWG, 60A Size 12, 25A Size 16, 13A	250V
	AHDBM04-24-91PR16-059	Size 24, 9 Pos, Kit, Receptacle, Pin, DuraMate™ AHDBM ISOBUS 91 Series, Metal, Reduced Seal, Wide Thread Adapter, Cable Clamp Backshell, Breakway-Ready, Size 8 Contact, 6AWG/16mm² Wire Seal Note: Use AT60-204-08141-16 contacts for 6AWG/16mm² applications	Size 8, 6AWG, 60A Size 12, 25A Size 16, 13A	250V

DuraMate[™] AHDM/AHDBM ISOBUS 91 Series - Backshell Options and Accessories

Image	Part Number	Description
	AHDMBS-24-002	Size 24, Backshell, 2 PC, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	AHDMBS-24-001	Size 24, Backshell, Tie Wrap, End Bell, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	AHDMBS-24-059	Size 24, Backshell, w Cable Clamp, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	AHDMBS-24-SM01	Size 24, Backshell, Metal, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	AHDM-BS-24NUT	Size 24, Adapter for use with: AHDPBS-010-2405 AHDP Backshell, Conduit, Snap-Over, Straight 180 AHDPBS-011-2405 AHDP Backshell, Conduit, Snap-Over, Right Angle 90
	AHDC34-24	Size 24, Protective Cap for Plug, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	AHDC36-24	Size 24, Protective Cap for Receptacle, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	A112264	Size 24, Lockwasher, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	A112263-90	Size 24, Nut, DuraMate™ AHDM/AHDBM ISOBUS 91 Series
	A114018	Size 8, Blank Seal Plug
	A114017	Size 12/16, Blank Seal Plug
<u> </u>	AT13-217-1605	Size 16, Locking Seal Plug

DuraMate[™] AHDM/AHDBM ISOBUS 91 Series - Backshell Options and Accessories, cont.

lmage	Part Number	Description
	AT11-310-1605	Size 16, Contact Removal Tool, Light Blue, 16-20AWG
	AT11-337-1205	Size 12 , Contact Removal Tool, Orange, 12-14AWG
	AT11-001-3.6M	Size 8, Contact Removal Tool, Black, 7-10AWG
	AT114008	Size 8, Contact Removal Tool, Green, 8-10AWG
All Sections of the Section of the S	AT60-204-08141-16	Size 8, 6AWG/16mm² Wire Range, Contact, Pin, Nickel-plated Note: Refer to Plug/Receptacle datasheets for a complete list of available contacts
	AT62-203-08141-16	Size 8, 6AWG/16mm² Wire Range, Contact, Socket, Nickel-plated Note: Refer to Plug/Receptacle datasheets for a complete list of available contacts

For more information, contact: Customer Service, +1 800 394 7732, csr@amphenol-sine.com

© 2022 Amphenol Sine Systems Corporation, 44274 Morley Drive, Clinton Township MI 48036 USA. www.amphenol-sine.com. Customer Service +1 800 394 7732 Every effort has been made to ensure that the information contained in this document is accurate at the time of publication. Specifications or information stated in this document are subject to change without notice. 02/2022