#### Cable Assemblies - Outdoor

## PT/MPO Cable Assemblies

The harsh environment PT/MPO plug assemblies and mating receptacles leverage the proven MIL spec 26482 connector system to provide an environmental seal and mechanical protection for 4 to 24 fiber MPO style connections.

The metal bayonet connector system is quick to deploy, requiring only  $\frac{1}{4}$  turn. It is a metal construction and has a positive latching system (both audible and visual).



Factory terminated PT/MPO plug assemblies are available in lengths starting from 1 meter and can be provided as

jumpers with a breakout to connect with most any industry standard optical connectors, allowing hassle free integration. The PT/MPO receptacle accepts industry standard MPO patch cables to be used inside the enclosure, allowing simple connection to QSFP devices, or can be used with a breakout cable for discrete single fiber or SFP connections. Amphenol's PT/MPO connectors are exceptionally suited for WiMax, LTE, and other applications requiring more than 2 fibers. The PT/MPO is capable of performing in even the toughest environments.

## **Features and Benefits**

Available in both Singlemode and Multimode fiber types

Available in 4, 8, 12 or 24 fiber configurations

**Excellent Vibration Characteristics** 

Mates to Standard MPO or MTP assemblies

## Specifications

Multimode IL: ≤0.25dB Typical <0.75dB Max.

Singlemode IL: ≤0.35dB Typical <0.75dB Max.

Return Loss: ≤-55dB

Operating Temperature: -40° to 85°C

Durability: >200 mating cycles

> 100 lb. Strain Relief

## Applications

FTTA

Outdoor Areas Harsh Environment

## **Industry Compliance**


Connectors are mechanically and optically intermateable with industry standard connectors and adapters and conform to TIA/EIA, IEC, and Telcordia specifications

GR-326 Issue IV



#### PT/MPO Plug Assembly

PT/MPO Rear Mount Receptacle 955-220-5001



# **Ordering Information**

1	Part Number	Description
	942-98281-10001	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
	942-98281-10001	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
	942-98281-10001	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
	942-98281-10001	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
	942-98281-10001	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
	942-98465-10001	JUMPER, LC/UPC(D)-LC/UPC(D) MICRO, 2F, S/M, 1M
	942-98XXX-10003	JUMPER, AARC PLUG-LC 2F, SM, OUTDOOR CABLE, 3M
	942-98XXX-1xxxx	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
1	943-98XXX-1xxxx	JUMPER, PT/MPO TO 2F AARC RECEPTACLE, 4F FLAT RIBBON
-	Sec	

\*Please call customer service for additional configurations