



ASGTC

Bayonet Coupling Connectors

ASGTCK-Q

Databus Bayonet Connectors

HVGTC

High Voltage Connectors

Ruggedized Connector Series for Rail & Mass Transit
and Other Harsh Environmental Applications

CONTENT

ASGTC SERIES

CONNECTOR STRUCTURE.....	2
MAIN CHARACTERISTICS	4
INSERT ARRANGEMENT.....	6
PRODUCT SERIES OVERVIEW.....	7
HOW TO ORDER.....	8
RECEPTACLE.....	9
PLUG.....	14
ATTACHMENT: PROTECTION CAP.....	18
BLIND CONTACTS.....	19
CONTACTS.....	20
TOOLS.....	21
WIRING INSTRUCTION	22
CONNECTOR MOUNTED INSTRUCTION.....	23

ASGTCK-QUADRAX SERIES


MAIN CHARACTERISTICS	25
INSERT ARRANGEMENT.....	26
MODULES & CONNECTOR.....	27
MEASURED DRAWING.....	28
ASGTCK 20-M1	30
ASGTCK 28-M2.....	31
ASGTCK 28-M3.....	33
ASGTCK 32-M3.....	34
ASGTCK 32-M4.....	35
ASGTCK 36-M4.....	36
ASGTCK 40-M7.....	38
QUADRAX CONTACT & CONTACT.....	40
TOOLS.....	42

HVGTC SERIES.....


MAIN CHARACTERISTICS	44
HOW TO ORDER.....	45
HVGTC 2001 500V	46
HVGTC 3201 3000V.....	47
HVGTC 3601 3000V.....	49
HVGTC 3603 2000V.....	50
HVGTCN 4003 2500V.....	53
HVGTCN 4004 2000V.....	54
HVGTC 4803 3000V.....	55
HVGTCN 4804 3000V / 500V.....	56
HVGTC 4806 3000V / 500V.....	57
PANEL MOUNTED DIMENSIONS.....	58
TOOLS.....	59

CONNECTOR STRUCTURE

PLUG



RECEPTACLE



PRODUCT INTRODUCTION

- ASGTC Series connector designed for railway and mass transit industry, including ASGTC, ASGTCN, ASGTCK.
- It's environmental cylindrical reverse bayonet coupling connector with self-locking system, which guarantee a fast locking and unlocking.
- High performance, rugged sealed connector with waterproof IP67 rated, robust shells for high temperature resistance and resistant to vibrations and shocks.

ASGTC: With self-locking system



ASGTCN: 1 key without self-locking system




INTRODUCTION

- ASGTCK It's environmental cylindrical reverse bayonet coupling connector with self-locking system (upon request) and alternate position.
- ASGTCK: 3 key and with self-locking system



Alternate position





KEY FEATURES

Special safety locking system, durable for high vibration and shocking condition

Anti cross-plugging key in the shell

Resistant to vibrations and shocks

Various of insert arrangement available

Sealing, IP67

MECHANICAL	
Durability	≥ 500 mating cycles
Vibration & shock	According to TB2761-1996 / IEC 61373-1999 (GB/T 21563-2008) Category 2
Contact retention force	#16: 70N #12: 90N #8: 110N
ELECTRICAL	
Rated current	#16: 13A #12: 23A #8 (Normal): 46A #8 (Radsok): 70A #4: 80A
Rated voltage	PB/T133.1-2002 / IEC60077-1:1999. Refer to page 6
Dielectric withstand voltage	2Ui+2000V (1 min.)
Contact resistance NFF61030	#16: 2.5mΩ Max #12: 1.3mΩ Max #8: 0.9mΩ Max
Insulator resistance	≥ 5000MΩ (DC500V)
Temperature rise	≤ 60K
ENVIRONMENTAL	
Temperature range	-55°C to 125°C
Humidity	90% to 95% (40±2°C)
Sealing	IP67 (DIN EN 60529)
Salt spray	96h (Zinc), 48h (Nickel)
MATERIAL	
Shell	Alu.alloy, zinc, nickel or anodic oxidation plating
Inserts	Thermoplastic
Contact	Copper alloy, gold or silver plating
Sealing gasket	Silicon rubber

INSERT ARRANGEMENT

FRONT FACE OF RECEPTACLE

CONTACTS



16



12









8



4



0



Insert arrangement 20-01
Rated voltage 800V
Rated current 46A
Contact number 1
Contact size #8
Withstanding voltage 3500V







20-03
500V
23A
3
#12
3000V

20-05
500V
13A
5
#16
3000V

20-07
500V
13A
7
#16
3000V

24-03
630V
46A(Normal)/70A(Radsok)
3
#8
3200V

24-M4
500V
46A
4
#8
3000V



Insert arrangement 24-07
Rated voltage 500V
Rated current 23A
Contact number 7
Contact size #12
Withstanding voltage 3000V






24-09
500V
13A
9
#16
3000V

24-M2
250V
46A/13A
10
2X#8,8X#16
2500V

24-M3
250V
23A
9
#12
2500V

24-M5
500V
80A/23A
2X#4,3X#12
#4,#12
3000V

28-12
500V
13A
12
#16
3000V







Insert arrangement 28-19
Rated voltage 320V
Rated current 13A
Contact number 19
Contact size #16
Withstanding voltage 2600V

32-07
500V
70A(Radsok)
7
#8
3000V

32-19
320V
23A
19
#12
2600V

36-03
500V
70A(Radsok)
3
#4
3000V

36-04
500V
70A(Radsok)
4
#4
3000V



Insert arrangement 36-24
Rated voltage 320V
Rated current 23A
Contact number 24
Contact size #12
Withstanding voltage 2600V

36-27
500V
13A
27
#16
3000V

36-48
320V
13A
48
#16
2600V

36-55
320V
13A
55
#16
2600V

Cable mounted receptacle ASGTC0L-D	Cable mounted receptacle ASGTC1L-D	Cable mounted receptacle ASGTC0L-LF	Cable mounted receptacle ASGTC1L-LF
			
Cable mounted receptacle ASGTC2L	Cable mounted receptacle ASGTC3L	Wall mounted receptacle ASGTC3A	Straight plug ASGTC6L-D
			
Straight plug ASGTC6L-A	Straight plug ASGTC6L-LF	Straight plug ASGTC6A-B	R/A plug ASGTC8A-LF
			
Receptacle protection cap ASGTC25043-LC	Plug protection cap ASGTC25042-LC	Male & female contact	Sealing plug
			

HOW TO ORDER

ASGTC 6 L 20 01 S C A / / X

ASGTC: With self-locking system

ASGTCN: 1 key without self-locking system

ASGTCK: 3 key and with self-locking system

Connector type:

- 0:** Cable mounted receptacle (Circular flange)
- 1:** Cable mounted receptacle (Square flange)
- 2:** Wall or box mounted receptacle (Circular flange)
- 3:** Wall or box mounted receptacle (Square flange)
- 5:** Jam nut receptacle
- 6:** Straight plug
- 8:** R/A plug

Service class:

- L:** Water proof
- A:** Non-watertight

Shell size:

20, 24, 28, 32, 36

Insert arrangement:

Please refer to P6

Contact type:

- P:** Pin
- S:** Socket

Contact wire type:

- C:** Crimp
- M:** Screw

Backshell:

- A:** Cable clamp without sleeve
- B:** Cable clamp with sleeve
- D:** Nut
- LF:** With hoop
- M:** Metric thread
- PG:** PG thread

Cable entry size:

(A,B,D) 20: Φ20, others please refer to page 9 to 15

(M) 25: M25 thread, other size please contact us.

(PG) 21: PG21 thread

Shell plating:


- Omit:** Olive drab zinc
- BA:** Black Anodized
- GA:** Green Anodized
- HA:** Hard Anodized
- BZ:** Black zinc
- NI:** Nickel

Alternate position (For ASGTCK):

- W:** 210°
- X:** 240°
- Y:** 270°
- Z:** 300°


WATERPROOF RECEPTACLE

CABLE MOUNTED RECEPTACLE (MALE CONTACT) (CIRCULAR FLANGE) ASGTC0L-D: FOR CABLE



Insert arrangement	Shell size	Contact number	$\Phi A \pm 1.2$	$B \pm 0.2$	$\Phi D \pm 0.8$	$E \pm 5$	$\Phi F \pm 0.8$	ΦG Ref.	$\Phi H \pm 0.8$
20-01	20	1 x #8	57	33	35	105	36	8.0	10
20-03	20	3 x #12	57	33	35	105	36	6.5	20
20-05	20	5 x #16	57	33	35	105	36	4.6	20
20-07	20	7 x #16	57	33	35	105	36	4.6	20
24-03	24	3 x #8	66	38	41.5	110	42	8.0	22
24-07	24	7 x #12	66	38	41.5	110	42	6.5	22
24-09	24	9 x #16	66	38	41.5	110	42	5.5	22
24-M2	24	8 x #16 + 2 x #8	66	38	41.5	110	42	4.6	22
24-M3	24	9 x #12	66	38	41.5	110	42	4.6 / 8.0	22
24-M4	24	4 x #8	66	38	41.5	110	42	8.0	22
24-M5	24	3 x #12 + 2 x #4	66	38	41.5	110	42	6.5 / 11.0	22
28-12	28	12 x #16	70	42	46.5	115	47	4.6	25
28-19	28	19 x #16	70	42	46.5	115	47	4.6	25
32-07	32	7 x #8	75	46	53	120	53	8.0	26
32-19	32	19 x #12	75	46	53	120	53	6.5	26
36-03	36	3 x #4	85	52	58.5	130	60	15.5	28
36-04	36	4 x #4	85	52	58.5	130	60	15.5	28
36-24	36	24 x #16	85	52	58.5	130	60	6.0	31
36-27	36	27 x #16	85	52	58.5	130	60	4.6	31
36-48	36	48 x #16	85	52	58.5	130	60	4.6	31
36-55	36	55 x #16	85	52	58.5	130	60	4.4	31

CABLE MOUNTED RECEPTACLE (MALE CONTACT) (SQUARE FLANGE) ASGTC1L-D: FOR CABLE




Insert arrangement	Shell size	Contact number	$A \pm 1.2$	$B \pm 0.2$	$\Phi D \pm 0.8$	$E \pm 5$	$\Phi F \pm 0.8$	ΦG Ref.	$\Phi H \pm 0.8$
20-01	20	1 x #8	43	33	35	105	36	8.0	10
20-03	20	3 x #12	43	33	35	105	36	6.5	20
20-05	20	5 x #16	43	33	35	105	36	4.6	20
20-07	20	7 x #16	43	33	35	105	36	4.6	20
24-03	24	3x #8	50	38	41.5	110	42	8.0	22
24-07	24	7 x #12	50	38	41.5	110	42	6.5	22
24-09	24	9 x #16	50	38	41.5	110	42	4.6	22
24-M2	24	8 x #16 + 2 x #8	50	38	41.5	110	42	4.6 / 8.0	22
24-M3	24	9 x #12	50	38	41.5	110	42	6.5	22
24-M4	24	4 x #8	50	38	41.5	110	42	8.0	22
24-M5	24	3 x #12 + 2 x #4	50	38	41.5	110	42	6.5 / 11.0	22
28-12	28	12 x #16	54	42	46.5	115	47	4.6	25
28-19	28	19 x #16	54	42	46.5	115	47	4.6	25
32-07	32	7 x #8	59	46	53	120	53	8.0	26
32-19	32	19 x #12	59	46	53	120	53	6.5	26
36-03	36	3 x #4	65	52	58.5	120	60	15.5	28
36-04	36	4 x #4	65	52	58.5	120	60	15.5	28
36-24	36	24 x #16	65	52	58.5	130	60	6.0	31
36-27	36	27 x #16	65	52	58.5	130	60	4.6	31
36-48	36	48 x #16	65	52	58.5	130	60	4.6	31
36-55	36	55 x #16	65	52	58.5	130	60	4.4	31

RECEPTACLES

WATERPROOF RECEPTACLE

CABLE MOUNTED RECEPTACLE (MALE CONTACT) (CIRCULAR FLANGE)


ASGTC0L-LF: FOR WIRE



Insert arrangement	Shell size	Contact number	$\Phi A \pm 1.2$	$B \pm 0.2$	$\Phi D \pm 0.8$	$E \pm 5$	$\Phi F \pm 0.8$	ΦG Ref.
20-01	20	1 x #8	57	33	35	90	26	5.5
20-03	20	3 x #12	57	33	35	90	26	4.0
20-05	20	5 x #16	57	33	35	90	26	3.5
20-07	20	7 x #16	57	33	35	90	26	3.5
24-03	24	3 x #8	66	38	41.5	90	31	5.5
24-07	24	7 x #12	66	38	41.5	90	31	4.0
24-09	24	9 x #16	66	38	41.5	90	31	3.5
24-M2	24	8 x #16 + 2 x #8	66	38	41.5	90	31	3.5 / 5.5
24-M3	24	9 x #12	66	38	41.5	90	31	5.5
24-M4	24	4 x #8	66	38	41.5	90	31	8.0
24-M5	24	3 x #12 + 2 x #4	66	38	41.5	90	31	6.5 / 11
28-12	28	12 x #16	70	42	46.5	90	36	3.5
28-19	28	19 x #16	70	42	46.5	90	36	3.2
32-07	32	7 x #8	75	46	53	90	43	8.0
32-19	32	19 x #12	75	46	53	90	43	4.0
36-03	36	3 x #4	101	52	58.5	101	48	12
36-04	36	4 x #4	101	52	58.5	101	48	12
36-24	36	24 x #16	85	52	58.5	90	48	4.0
36-27	36	27 x #16	85	52	58.5	90	48	3.6
36-48	36	48 x #16	85	52	58.5	90	48	3.6

CABLE MOUNTED RECEPTACLE (MALE CONTACT) (SQUARE FLANGE)


ASGTC1L-LF: FOR WIRE



Insert arrangement	Shell size	Contact number	$A \pm 1.2$	$B \pm 0.2$	$\Phi D \pm 0.8$	$E \pm 5$	$\Phi F \pm 0.8$	ΦG Ref.
20-01	20	1 x #8	43	33	35	90	26	5.5
20-03	20	3 x #12	43	33	35	90	26	4.0
20-05	20	5 x #16	43	33	35	90	26	3.5
20-07	20	7 x #16	43	33	35	90	26	3.5
24-03	24	3 x #8	50	38	41.5	90	31	5.5
24-07	24	7 x #12	50	38	41.5	90	31	4.0
24-09	24	9 x #16	50	38	41.5	90	31	3.5
24-M2	24	8 x #16 + 2 x #8	50	38	41.5	90	31	3.5 / 5.5
24-M3	24	9 x #12	50	38	41.5	90	31	5.5
24-M4	24	4 x #8	50	38	41.5	90	31	8.0
24-M5	24	3 x #12 + 2 x #4	50	38	41.5	90	31	6.5 / 11
28-12	28	12 x #16	54	42	46.5	90	36	3.5
28-19	28	19 x #16	54	42	46.5	90	36	3.2
32-07	32	7 x #8	59	46	53	90	43	8.0
32-19	32	19 x #12	59	46	53	90	43	4.0
36-03	36	3 x #4	65	52	58.5	101	48	12
36-04	36	4 x #4	65	52	58.5	101	48	12
36-24	36	24 x #16	65	52	58.5	90	48	4.0
36-27	36	27 x #16	65	52	58.5	90	48	3.6
36-48	36	48 x #16	65	52	58.5	90	48	3.6


WATERPROOF RECEPTACLE

CABLE MOUNTED RECEPTACLE (MALE CONTACT) (CIRCULAR FLANGE) ASGTC1L-M: FOR WIRE



Insert arrangement	Shell size	Contact number	$\Phi A \pm 1.2$	$B \pm 0.2$	$\Phi D \pm 0.8$	$E \pm 5$	$\Phi G \text{ Ref.}$	M
20-01	20	1 x #8	43	33	35	135	5.5	M16
20-03	20	3 x #12	43	33	35	135	4	M16
20-05	20	5 x #16	43	33	35	135	3.5	M20
20-07	20	7 x #16	43	33	35	135	3.5	M20
24-03	24	3 x #8	50	38	42	140	5.5	M20
24-07	24	7 x #12	50	38	42	140	4.0	M25
24-09	24	9 x #16	50	38	42	140	3.5	M25
24-M2	24	8 x #16 + 2 x #8	50	38	42	140	3.5 / 5.5	M25
24-M3	24	9 x #12	50	38	42	140	5.5	M25
24-M4	24	4 x #8	50	38	42	140	8.0	M25
24-M5	24	3 x #12 + 2 x #4	50	38	42	140	6.5 / 11	M25
28-12	28	12 x #16	52	42	46	145	3.5	M25
28-19	28	19 x #16	52	42	46	145	3.2	M25
32-07	32	7 x #8	59	46	53	145	8.0	M25
32-19	32	19 x #12	59	46	53	145	4.0	M32
36-03	36	3 x #4	65	52	58	145	12	M32
36-04	36	4 x #4	65	52	58	145	12	M32
36-24	36	24 x #16	65	52	58	145	6	M32
36-27	36	27 x #16	65	52	58	145	3.5	M32
36-48	36	48 x #16	65	52	58	145	3.2	M40
36-55	36	55 x #16	65	52	58	145	3.2	M40

CABLE MOUNTED RECEPTACLE (MALE CONTACT) (SQUARE FLANGE) ASGTC1L-TD: FOR WIRE




Insert arrangement	Shell size	Contact number	$\Phi A \pm 1.2$	$B \pm 0.2$	$\Phi C \pm 0.8$	$E \pm 5$	$\Phi G \text{ Ref.}$
20-01	20	1 x #8	43	33	10	75	5.5
20-03	20	3 x #12	43	33	10	75	4
20-05	20	5 x #16	43	33	10	75	3.5
20-07	20	7 x #16	43	33	10	75	3.5
24-03	24	3 x #8	50	38	15	80	5.5
24-07	24	7 x #12	50	38	15	80	4.5
24-09	24	9 x #16	50	38	15	80	3.5
24-M2	24	8 x #16 + 2 x #8	50	38	15	80	3.5 / 5.5
24-M3	24	9 x #12	50	38	15	80	5.5
24-M4	24	4 x #8	50	38	15	80	8.0
24-M5	24	3 x #12 + 2 x #4	50	38	15	80	6.5 / 11
28-12	28	12 x #16	54	42	18	83	3.5
28-19	28	19 x #16	54	42	20	83	3.2
32-07	32	7 x #8	59	46	20	83	8.0
32-19	32	19 x #12	59	46	20	83	4.0
36-03	36	3 x #4	65	52	25	83	12
36-04	36	4 x #4	65	52	25	83	12
36-24	36	24 x #16	65	52	25	83	6
36-27	36	27 x #16	65	52	25	83	3.5
36-48	36	48 x #16	65	52	25	83	3.2
36-55	36	55 x #16	65	52	25	83	3.2

RECEPTACLES

WATERPROOF RECEPTACLE

WALL MOUNTED / BOX MOUNTED RECEPTACLE (MALE CONTACT) (CIRCULAR FLANGE)


ASGTC2L: FOR WIRE



Insert arrangement	Shell size	Contact number	$\phi A \pm 1.2$	$B \pm 0.2$	$\phi D \pm 0.8$	$E \pm 5$	$\phi F \pm 0.8$	$\phi G \text{ Ref.}$
20-01	20	1 x #8	57	33	35	54	36	8.0
20-03	20	3 x #12	57	33	35	54	36	6.5
20-05	20	5 x #16	57	33	35	54	36	4.6
20-07	20	7 x #16	57	33	35	54	36	4.6
24-03	24	3 x #8	66	38	41.5	63	42	8.0
24-07	24	7 x #12	66	38	41.5	63	42	6.5
24-09	24	9 x #16	66	38	41.5	63	42	4.6
24-M2	24	8 x #16 + 2 x #8	66	38	41.5	63	42	4.6 / 8.0
24-M3	24	9 x #12	66	38	41.5	63	42	6.5
24-M4	24	4 x #8	66	38	41.5	63	42	8.0
24-M5	24	3 x #12 + 2 x #4	66	38	41.5	63	42	6.5 / 11
28-12	28	12 x #16	70	42	46.5	54	47	4.6
28-19	28	19 x #16	70	42	46.5	54	47	4.6
32-07	32	7 x #8	75	46	53	54	53	8.0
32-19	32	19 x #12	75	46	53	54	53	6.5
36-24	36	24 x #16	85	52	58.5	54	60	4.3
36-27	36	27 x #16	85	52	58.5	54	60	4.6
36-48	36	48 x #16	85	52	58.5	54	60	4.6
36-55	36	55 x #16	85	52	58.5	54	60	4.5

WALL MOUNTED OR BOX MOUNTED RECEPTACLE (MALE CONTACT) (SQUARE FLANGE)


ASGTC3L: FOR WIRE



Insert arrangement	Shell size	Contact number	$A \pm 1.2$	$B \pm 0.2$	$\phi D \pm 0.8$	$E \pm 5$	$\phi F \pm 0.8$	$\phi G \text{ Ref.}$
20-01	20	1 x #8	43	33	35	54	36	8.0
20-03	20	3 x #12	43	33	35	54	36	6.5
20-05	20	5 x #16	43	33	35	54	36	4.6
20-07	20	7 x #16	43	33	35	54	36	4.6
24-03	24	3 x #8	50	38	41.5	63	42	8.0
24-07	24	7 x #12	50	38	41.5	63	42	6.5
24-09	24	9 x #16	50	38	41.5	63	42	4.6
24-M2	24	8 x #16 + 2 x #8	50	38	41.5	63	42	4.6 / 8.0
24-M3	24	9 x #12	50	38	41.5	63	42	6.5
24-M4	24	4 x #8	50	38	41.5	63	42	8.0
24-M5	24	3 x #12 + 2 x #4	50	38	41.5	63	42	6.5 / 11
28-12	28	12 x #16	54	42	46.5	54	47	4.6
28-19	28	19 x #16	54	42	46.5	54	47	4.6
32-07	32	7 x #8	59	46	53	54	53	8.0
32-19	32	19 x #12	59	46	53	54	53	6.5
36-24	36	24 x #16	65	52	58.5	54	60	4.3
36-27	36	27 x #16	65	52	58.5	54	60	4.8
36-48	36	48 x #16	65	52	58.5	54	60	4.5
36-55	36	55 x #16	65	52	58.5	54	60	4.5



WALL MOUNTED OR BOX MOUNTED RECEPTACLE (MALE CONTACT) (SQUARE FLANGE)

ASGTC3A




Insert arrangement	Shell size	Contact number	A ± 1.2	B ± 0.2	$\Phi D \pm 0.8$	E ± 5	$\Phi F \pm 0.8$	ΦG Ref.
20-01	20	1 x #8	43	33	35	42	30	8.0
20-03	20	3 x #12	43	33	35	42	30	6.5
20-05	20	5 x #16	43	33	35	42	30	4.6
20-07	20	7 x #16	43	33	35	42	30	4.6
24-03	24	3 x #8	50	38	41.5	49	36	8.0
24-07	24	7 x #12	50	38	41.5	49	36	6.5
24-09	24	9 x #16	50	38	41.5	49	36	4.6
24-M2	24	8 x #16 + 2 x #8	50	38	41.5	49	36	4.6 / 8.0
24-M3	24	9 x #12	50	38	41.5	49	36	6.5
24-M4	24	4 x #8	50	38	41.5	56	36	8.0
24-M5	24	3 x #12 + 2 x #4	50	38	41.5	56	36	6.5 / 11
28-12	28	12 x #16	54	42	46.5	42	41	4.6
28-19	28	19 x #16	54	42	46.5	42	41	4.6
32-07	32	7 x #8	59	46	53	42	47	8.0
32-19	32	19 x #12	59	46	53	42	47	6.5
36-24	36	24 x #16	65	52	58.5	42	54	6.0
36-27	36	27 x #16	65	52	58.5	42	54	4.6
36-48	36	48 x #16	65	52	58.5	42	54	4.6
36-55	36	55 x #16	65	52	58.5	42	54	4.4

PANEL MOUNTED DIMENSIONS



Front mounted



Rear mounted

Dimension: mm

Shell size	$\Phi A(\pm_0^1)$	B ± 0.2	$\Phi C \pm 0.2$
	Front / Rear Mounted		
20	36	33	5.5
24	42.5	38	5.5
28	47.5	42	5.5
32	54	46	5.5
36	59.5	52	5.5


Remark: Panel thickness below 5mm for rear mounted and must use with nut.

PLUGS

WATERPROOF PLUG

STRAIGHT PLUG (FEMALE CONTACT)


ASGTC6L-D: FOR CABLE



Insert arrangement	Shell size	Contact number	$\phi A \pm 0.8$	$B \pm 5$	$\phi C \pm 0.8$	$\phi G \text{ Ref.}$
20-01	20	1 x #8	45	100	10	8.0
20-03	20	3 x #12	45	100	20	6.5
20-05	20	5 x #16	45	100	20	4.6
20-07	20	7 x #16	45	100	20	4.6
24-03	24	3 x #8	50	110	22	8.0
24-07	24	7 x #12	50	110	22	6.5
24-09	24	9 x #16	50	110	22	4.6
24-M2	24	8 x #16 + 2 x #8	50	110	22	4.6 / 8.0
24-M3	24	9 x #12	50	110	22	6.5
24-M4	24	4 x #8	50	110	22	8.0
24-M5	24	3 x #12 + 2 x #4	50	110	22	6.5 / 11
28-12	28	12 x #16	56	110	25	4.6
28-19	28	19 x #16	56	110	25	4.6
32-07	32	7 x #8	62	115	26	8.0
32-19	32	19 x #12	62	115	26	6.5
36-03	36	3 x #4	68	135	28	15.5
36-04	36	4 x #4	68	135	28	15.5
36-24	36	24 x #16	68	125	31	6.0
36-27	36	27 x #16	68	125	31	5.5
36-48	36	48 x #16	68	125	31	4.5
36-55	36	55 x #16	68	125	31	4.4

STRAIGHT PLUG (FEMALE CONTACT) WITH CABLE CLAMP BACKSHELL

ASGTC6L-A: FOR CABLE




Insert arrangement	Shell size	$\phi A \pm 0.8$	$B \pm 5$	$\phi C \pm 0.8$	$\phi G \text{ Ref.}$
20-07	20	45	115	20	4.6
36-24	36	68	154	31.5	6.0
36-27	36	68	154	31.5	4.6
36-48	36	68	154	31.5	4.6
36-55	36	68	154	31.5	4.4

WATERPROOF PLUG


STRAIGHT PLUG (FEMALE CONTACT)

ASGTC6L-LF: FOR WIRE



Insert arrangement	Shell size	Contact number	$\phi A \pm 0.8$	$B \pm 5$	$\phi C \pm 0.8$	$\phi G \text{ Ref.}$
20-01	20	1 x #8	45	85	26	5.5
20-03	20	3 x #12	45	85	26	4.0
20-05	20	5 x #16	45	85	26	3.5
20-07	20	7 x #16	45	85	26	3.5
24-03	24	3 x #8	50	85	31	5.5
24-07	24	7 x #12	50	85	31	4.0
24-09	24	9 x #16	50	85	31	3.5
24-M2	24	8 x #16 + 2 x #8	50	85	31	3.5 / 5.5
24-M3	24	9 x #12	50	85	31	5.5
24-M4	24	4 x #8	50	85	31	8.0
24-M5	24	3 x #12 + 2 x #4	50	85	31	6.5 / 11
28-12	28	12 x #16	56	85	36	3.5
28-19	28	19 x #16	56	85	36	3.2
32-07	32	7 x #8	62	85	43	8.0
32-19	32	19 x #12	62	85	43	4.0
36-03	36	3 x #4	68	101	48	12.0
36-04	36	4 x #4	68	101	48	12.0
36-24	36	24 x #16	68	85	48	4.0
36-27	36	27 x #16	68	85	48	3.6
36-48	36	48 x #16	68	85	48	3.6

PLUG, TERMINATION WITH THREAD & PG ADAPTER
ASGTC6L-M / PGXX: FOR CABLE PROTECTION TUBE





Insert arrangement	Shell size	Contact number	$\phi A \pm 0.8$	$B \pm 5$	M	$\phi G \text{ Ref.}$
20-01	20	1 x #8	45	71	PG9	8.0
20-07	20	7 x #16	45	71	M25	5.5
24-03	24	3 x #8	50	71	M25	8.0
24-07	24	7 x #12	50	71	M25	6.5
24-09	24	9 x #16	50	71	M25	5.5
24-M2	24	8 x #16 + 2 x #8	50	71	M25	5.5 / 8.0
24-M3	24	9 x #12	50	71	M25	6.5
24-M4	24	4 x #8	50	71	M25	8.0
24-M5	24	3 x #12 + 2 x #4	50	71	M25	6.5 / 11
28-12	28	12 x #16	56	71	M25	4.6
28-19	28	19 x #16	56	71	M25	4.6
32-07	32	7 x #8	62	71	M32	8.0
36-24	36	24 x #16	68	71	M32	6.0
36-27	36	27 x #16	68	71	PG29	5.5
36-48	36	48 x #16	68	71	PG36	4.5
36-55	36	55 x #16	68	71	M40	4.4

PLUGS

WATERPROOF PLUG

STRAIGHT PLUG (FEMALE CONTACT) ASGTC6L-TD: FOR WIRE




Insert arrangement	Shell size	Contact number	$\Phi A \pm 0.8$	$B \pm 5$	$\Phi C \pm 0.8$	ΦG Ref.
20-01	20	1 x #8	45	130	10	5.5
20-03	20	3 x #12	45	130	10	4
20-05	20	5 x #16	45	130	10	3.5
20-07	20	7 x #16	45	130	10	3.5
24-03	24	3 x #8	50	135	15	5.5
24-07	24	7 x #12	50	135	15	4
24-09	24	9 x #16	50	135	15	3.5
24-M2	24	8 x #16 + 2 x #8	50	135	15	3.5 / 5.5
24-M3	24	9 x #12	50	135	15	5.5
24-M4	24	4 x #8	50	135	15	8.0
24-M5	24	3 x #12 + 2 x #4	50	135	15	6.5 / 11
28-12	28	12 x #16	56	140	18	3.5
28-19	28	19 x #16	56	140	20	3.2
32-07	32	7 x #8	62	140	20	8.0
32-19	32	19 x #12	62	140	20	4.0
36-03	36	3 x #4	68	140	25	12
36-04	36	4 x #4	68	140	25	12
36-24	36	24 x #12	68	140	25	6
36-27	36	27 x #16	68	140	25	3.5
36-48	36	48 x #16	68	140	25	3.2
36-55	36	55 x #16	68	140	25	3.2

NON WATERPROOF PLUG

STRAIGHT PLUG (FEMALE CONTACT)


ASGTC6A-B: FOR CABLE



Insert arrangement	Shell size	Contact number	$\Phi A \pm 0.8$	$B \pm 5$	$\Phi C \pm 0.8$	$\Phi G \text{ Ref.}$
20-01	20	1 x #8	45	130	16	8.0
20-03	20	3 x #12	45	130	16	6.5
20-05	20	5 x #16	45	130	16	4.6
20-07	20	7 x #16	45	130	16	4.6
24-03	24	3 x #8	50	145	16	8.0
24-07	24	7 x #12	50	145	16	6.5
24-09	24	9 x #16	50	145	16	4.6
24-M2	24	8 x #16 + 2 x #8	50	145	19	4.6 / 8.0
24-M3	24	9 x #12	50	145	19	6.5
24-M4	24	4 x #8	66	145	19	8.0
24-M5	24	3 x #12 + 2 x #4	66	145	19	6.5 / 11
28-12	28	12 x #16	56	130	19	4.6
28-19	28	19 x #16	56	130	19	4.6
32-07	32	7 x #8	62	130	24	8.0
32-19	32	19 x #12	62	130	24	6.5
36-24	36	24 x #16	68	135	32	6.0
36-27	36	27 x #16	68	135	24	4.6
36-48	36	48 x #16	68	135	32	4.6
36-55	36	55 x #16	68	135	32	4.4

RIGHT ANGLE PLUG (FEMALE CONTACT)

ASGTC8A-B



Insert arrangement	Shell size	Contact number	$\Phi A \pm 0.8$	$B \pm 5$	$C \pm 1.2$	$D \pm 5$	$\Phi E \pm 0.8$	$\Phi G \text{ Ref.}$
20-01	20	1 x #8	45	130	37	98	16	8.0
20-03	20	3 x #12	45	130	37	98	16	6.5
20-05	20	5 x #16	45	130	37	98	16	4.6
20-07	20	7 x #16	45	130	37	98	16	4.6
24-03	24	3 x #8	50	145	37	98	16	8.0
24-07	24	7 x #12	50	145	37	98	16	6.5
24-09	24	9 x #16	50	145	37	98	16	4.6
24-M2	24	8 x #16 + 2x #8	50	145	43	98	19	4.6 / 8.0
24-M3	24	9 x #12	50	145	43	98	19	6.5
24-M4	24	4 x #8	66	145	43	98	19	8.0
24-M5	24	3 x #12 + 2 x #4	66	145	43	98	19	6.5 / 11
28-12	28	12 x #16	56	130	43	100	19	4.6
28-19	28	19 x #16	56	130	43	100	19	4.6
32-07	32	7 x #8	62	130	51	100	24	8.0
32-19	32	19 x #12	62	130	51	100	24	6.5
36-24	36	24 x #16	68	135	57	102	32	6.0
36-27	36	27 x #16	68	135	57	102	32	4.6
36-48	36	48 x #16	68	135	57	102	32	4.6
36-55	36	55 x #16	68	135	57	102	32	4.4


PROTECTION CAP

HOW TO ORDER: PROTECTION CAP

	ASGTC	25043	20	LC	/
ASGTC: With self-locking system					
Connector type:					
25042: Plug protection cap					
25043: Receptacle protection cap					
Shell size: 20, 24, 28, 32, 36					
Shell plating:					
Omit: Olive drab zinc					
BA: Black Anodized					
GA: Green Anodized					
HA: Hard Anodized					
BZ: Black zinc					
NI: Nickel					

PLUG PROTECTION CAP

ASGTC25042




Part number / Size

For ASGTC Plug	Shell size	$\Phi A \pm 1.2$	$\Phi B \pm 0.5$
ASGTC25042-20LC	20	45	35
ASGTC25042-24LC	24	52	41.5
ASGTC25042-28LC	28	56	46
ASGTC25042-32LC	32	62	53
ASGTC25042-36LC	36	68	58

RECEPTACLE PROTECTION CAP

ASGTC25043



Part number / Size

For ASGTC Receptacle	Shell size	$\Phi A \pm 1.2$	$\Phi B \pm 0.5$
ASGTC25043-20LC	20	45	115
ASGTC25043-24LC	24	50	130
ASGTC25043-28LC	28	56	130
ASGTC25043-32LC	32	62	130
ASGTC25043-36LC	36	68	130


BLIND CONTACTS

SEALING PLUGS


CONTACTS

#16 BLIND CONTACTS P/N: C420004014

MATERIAL: STEEL / ZINC PLATED




SEALING PLUGS



Contact size	Part number	Color	ΦA	ΦB	C
#16	C220004202	Black	5	6	16.5
#12	C220004128	Black	4.7	6.5	17.5
#8	C220004129	Black	6	7	15

CONTACTS








CONTACTS



PIN




SOCKET



Contact size	Part number		Plating	Wire size	Tools		
	Pin	Socket			Crimping	Insertion	Extraction
#16	C42000400500(G)	C42000409500(G)	Silver(Gold)	1.0 to 1.5mm ²	M22520/1-01	AS-GTC-I-16	AS-GTC-R-16
	C42000400501(G)	C42000409501(G)	Silver(Gold)	0.5 to 1.0mm ²			
	C42000400502(G)	C42000409502(G)	Silver(Gold)	1.5 to 2.0mm ²			
#12	C420003315	C420003316	Silver	1.5 to 2.0mm ²	M317	AS-GTC-I-12	AS-GTC-R-12
	C420003314	C420003309	Silver	2.5 to 4.0mm ²			
#8 (Radsok)	C420004103	C420004104	Silver	5.0 to 7.0mm ²	APHWA23KIT	AS-GTC-I-8	AS-GTC-R-8
	C420004112	C420004113	Silver	8.0 to 10mm ²			
#8 (Normal)	C420004114	C420004115	Silver	2.5 to 4.0mm ²			
	C420004116	C420004117	Silver	6.0 to 8.0mm ²			
	C420004112	C420004111	Silver	8.0 to 10mm ²			

Contact size	Cable section	Crimping	Insertion	Extraction	Force gauge
#16	0.5 to 2mm ²	M22520/1-01 (Manual)	ASGTC-I-16	ASGTC-R-16	ASGTC-TM-16
#12	2.5 to 4mm ²	M317 (Manual)	ASGTC-I-12	ASGTC-R-12	ASGTC-TM-12
#8	2.5 to 10mm ²	APHWA23KIT (Pneumatic)	ASGTC-I-8	ASGTC-R-8	ASGTC-TM-8

#16 Crimping tool M22520/1-01	#16 Insertion tool ASGTC-I-16	#16 Extraction tool ASGTC-R-16	#16 Force gauge ASGTC-TM-16
			
#12 Crimping tool: M317 (Localizer: TP805)	#12 Insertion tool ASGTC-I-12	#12 Extraction tool ASGTC-R-12	#12 Force gauge ASGTC-TM-12
			
#8 Crimping tool APHWA23KIT	#8 Insertion tool ASGTC-I-8	#18 Extraction tool ASGTC-R-8	#8 Force gauge ASGTC-TM-8
			

WIRING INSTRUCTIONS

WIRING INSTRUCTION



Tools		For contacts P/N	Section of conductor	A size
Crimping tool	Localizer			
M22520/1-01	UH2-5	C420004005XX C420004095XX	0.5 to 2.0mm ²	6 ⁺¹ ₀ mm

1. Cable preparing	4. Open the handle of crimp tools	7. Clench the tools handle until crimp well
2. Select the right localizer, screw into the tools	5. Put the contact into the localizer	8. Relax the handle, as below shows the status of the wire
3. Select the right size	6. Put the stripped wire into the tools	

1. Insert pin



2. Remove pin



3. Connector mounting



Fix and wrest the screw



ASGTCK Quadrax belongs to ASGTC series, which offers environmental cylindrical reverse bayonet coupling connectors.

Its rugged housing (IP67) is resistant to high temperatures, vibrations and shocks, providing a high performance, reliable connector.

Supporting a variety of data types, Amphenol ASGTC Quadrax circular bayonet databus connector allows designers to initiate data transfers from Ethernet, MVB, WTB, and video lines, according to VG95234 within the same

connector. Designed for railway and mass transit industry, this connector provides a rated current up to 13A and a 1000V (AC) max high-voltage.

ASGTCK Quadrax can use different kinds of cables including CAT 5E, CAT 6A, CAT 7, transmission speed up to 10 Gigabit/s (according to TIA568C.2 / ISO11801 standard), widely use in railway and mass transit industry, factory automation, servers and other devices. For any special request or custom order, please contact us.



Modular, secure and reliable reverse bayonet connection.



Different kinds of keyway offering different alternate positions.




High safety & speed in data transmission for MVB, WTB, Ethernet...




Gold plated contacts, which provide a 360 degrees of EMI shielding.


ALTERNATE POSITION




W: 210°



X: 240°



Y: 270°



Z: 300°

ASGTCK-Quadrax

- Special safety locking system, durable for high vibration and shocking condition
- Independent quadrax contacts
- EMI/RFI shielding
- Resistant to vibrations and shocks
- Safe and reliable data transmission
- Sealing, IP67



MECHANICAL

Durability	≥ 500 mating cycles
Connection type	Crimp
Vibration & shock	According to TB2761-1996 / IEC 61373-1999 (GB/T 21563-2008) Category 2
Contact retention force NFF 61030	#16: 70N #20: 70N #22: 44N

ENVIRONMENTAL

Temperature range	−55°C to 125°C
Humidity	90% to 95% (40±2°C)
Sealing	IP67
Salt spray	96h


MATERIAL

Shell	Alu. alloy, zinc plating
Quadrax pin	Copper alloy, silver plating
Inserts	Thermoplastic
Contact	Copper alloy, gold plating
Sealing gasket	Silicon rubber

ELECTRICAL



	Q4-contact	Q8-contact	Q4S-contact	QG (Quadrax Gigabit) (Gigabit Module)
Contact number	4 x #16	8 x #20	4 x #20	8 x #22
Rated current	13A	7.5A	7.5A	5A
Rated voltage	AC 125V (r.m.s)	AC 50V (r.m.s)	AC 50V (r.m.s)	AC 50V (r.m.s)
Withstanding voltage	AC 1500V (r.m.s)	AC 1000V (r.m.s)	AC 1000V (r.m.s)	AC 800V (r.m.s)
Contact resistance	≤ 2.5mΩ	≤ 3.0mΩ	≤ 3.0mΩ	≤ 5.0mΩ
Contact resistance		≥2000MΩ		≥100MΩ
Insertion loss		≤0.4dB@100MHz		≤0.3dB@250MHz
Return loss		≤20dB@100MHz		≤16dB@250MHz
Crosstalk loss		≥43dB@100MHz		≥46dB@250MHz
Transmission speed		1GB/S		10 GB/S
Category		Cat.5e		Cat.6a
Temperature rise		≤ 60K		





INSERT ARRANGEMENT



Insert arrangement	20-M1	20-M1	28-M2	28-M2
Rated voltage	125V	125v	125V	125V
Rated current	7.5A	7.5A	7.5A	7.5A
Module quantity	1	1	2	2
Module type	Q4	Q8	Q4	Q8
Category	CAT 5E	CAT 5E	CAT 5E	CAT 5E
Transmission speed	1 Gigabit/s	1 Gigabit/s	1 Gigabit/s	1 Gigabit/s

Insert arrangement	28-M2	28-M3	32-M3	32-M3
Rated voltage	50V	50V	125V	125V
Rated current	5A	7.5A	7.5A	7.5A
Module quantity	2	3	3	3
Module type	千兆	Q4S	Q4	Q8
Category	CAT 6A & CAT 7	CAT 5E	CAT 5E	CAT 5E
Transmission speed	10 Gigabit/s	1 Gigabit/s	1 Gigabit/s	1 Gigabit/s

				
Insert arrangement	32-M3	32-M4	36-M4	36-M4
Rated voltage	50V	50V	125V	125V
Rated current	5A	7.5A	7.5A	7.5A
Module quantity	3	4	4	4
Module type	千兆	Q4S	Q4	Q8
Category	CAT 6A & CAT 7	CAT 5E	CAT 5E	CAT 5E
Transmission speed	10 Gigabit/s	1 Gigabit/s	1 Gigabit/s	1 Gigabit/s

				
Insert arrangement	32-M4	40-M7	40-M7	40-M7
Rated voltage	50V	125V	125V	50V
Rated current	5A	7.5A	7.5A	5A
Module quantity	4	7	7	7
Module type	千兆	Q4	Q8	千兆
Category	CAT 6A & CAT 7	CAT 5E	CAT 5E	CAT 6A & CAT 7
Transmission speed	10 Gigabit/s	1 Gigabit/s	1 Gigabit/s	10 Gigabit/s

Available modules: Q4/Q4S/Q8/QG



QG Module connector

QG-CONTACT






Q4 Module connector


Q4-CONTACT



Measured drawing




Measured drawing




ASGTCK 20-M1
1 x Q-contact

ASGTCK6L-D, STRAIGHT PLUG, NUT TERMINATION
FOR CABLE




Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 20M1 PGC D8 LC	20-M1	20	1 x Q4 / Q8 / Gigabit (female)	$\phi 6$ to $\phi 8$

ASGTCK1L-D, RECEPTACLE, NUT TERMINATION
FOR CABLE




Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK1L 20M1 SGC D8 LC	20-M1	20	1 x Q4 / Q8 /QG (male)	$\phi 6$ to $\phi 8$

ASGTCK6L-LF, STRAIGHT PLUG, HOOP TERMINATION FOR 2PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 28M2 PGC 2D7 LF LC	28-M2	28	2 x Q4/Q8/QG (female)	Φ6 to Φ8


ASGTC6L-M, STRAIGHT PLUG, TERMINATION WITH THREAD FOR 2PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact
ASGTCK6L 28M2 PGC M25 LC	28-M2	28	2 x Q4Q4/Q8/QG (female)


ASGTCK1L-LF

ASGTCK1L-LF, RECEPTACLE, HOOP TERMINATION FOR 2PCS CABLE




Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK1L 28M2 SGC 2D7 LF LC	28-M2	28	2 x Q4/Q8/QG (male)	Φ6 to Φ8

ASGTCK3A, BOX MOUNTED RECEPTACLE




Part number	Insert arrangement	Shell size	Q-contact
ASGTCK3A 28M2 SGC LC	28-M2	28	2 x Q4/Q8/QG (male)

ASGTCK6L-D, STRAIGHT PLUG, NUT TERMINATION FOR CABLE




Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 28M3 SGC D24 LC	28-M3	28	3 x Q4S (female)	Φ20 to Φ24

ASGTCK6L-A, STRAIGHT PLUG, CABLE CLAMP TERMINATION FOR CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 28M3 SGC A24 LC	28-M3	28	3 x Q4S (female)	Φ20 to Φ24


ASGTCK0L-LF, RECEPTACLE, HOOP TERMINATION FOR 3PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK0L 28M3 PGC 3D7 LF LC	28-M3	28	3 x Q4S (male)	3 x Φ5 to Φ7

ASGTCK 32-M3
3 x Q-contact

ASGTCK6L-M, PLUG, TERMINATION WITH THREAD
FOR M25 ADAPTER




Part number	Insert arrangement	Shell size	Q-contact
ASGTCK6L 32M3 PGC M25 LC	32-M3	32	3 x Q4 / Q8 /QG (female)



ASGTCK1L-LF, RECEPTACLE, HOOP TERMINATION
FOR 3PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK1L 32M3 SGC 3D7 LF LC	32-M3	32	3 x Q4 / Q8/QG (male)	$\phi 6$ to $\phi 8$





ASGTCK6L-A, STRAIGHT PLUG, CABLE CLAMP TERMINATION FOR CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 32M4 SGC A24 LC	32-M4	32	4 x Q4S (female)	$\varnothing 20$ to $\varnothing 24$


ASGTCK0L-LF, RECEPTACLE, HOOP TERMINATION FOR 4PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK0L 32M4 PGC 4D7 LF LC	32-M4	32	4 x Q4S (male)	$\varnothing 5$ to $\varnothing 7$


ASGTCK 36-M4 4 x Q-contact

ASGTCK6L-LF, STRAIGHT PLUG, HOOP TERMINATION FOR 4PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 36M4 PGC 4D7 LF LC	36-M4	36	4 x Q4 / Q8/QG (female)	4 x $\phi 6$ to $\phi 8$

ASGTCK6L-M, PLUG, TERMINATION WITH THREAD FOR M32 ADAPTER




Part number	Insert arrangement	Shell size	Q-contact
ASGTCK6L 36M4 PGC M32 LC	36-M4	36	4 x Q4 / Q8/QG (female)


ASGTCK1L-LF, RECEPTACLE, HOOP TERMINATION FOR 4PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK1L 36M4 PGC 4D7 LC	36-M4	36	4 x Q4 / Q8 / QG (male)	4 x $\Phi 6$ to $\Phi 8$




ASGTCK3A, BOX MOUNTED RECEPTACLE



Part number	Insert arrangement	Shell size	Q-contact
ASGTCK3A 36M4 PGC LC	36-M4	36	4 x Q4 / Q8 / QG (male)


ASGTCK 40-M7
7 x Q-contact

ASGTCK6L-LF, STRAIGHT PLUG, HOOP TERMINATION
FOR 7PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK6L 40M7 PGC 7D7 LF LC	40-M7	40	7 x Q4 / Q8 / QG (female)	7x $\Phi 6$ to $\Phi 8$

ASGTCK6L-M, STRAIGHT PLUG, TERMINATION WITH THREAD
FOR M40 ADAPTER





Part number	Insert arrangement	Shell size	Q-contact
ASGTCK6L 40M7 PGC M40 LC	40-M7	40	7 x Q4 / Q8 / QG (female)



ASGTCK1L-LF, RECEPTACLE, HOOP TERMINATION
FOR 7PCS CABLE



Part number	Insert arrangement	Shell size	Q-contact	Cable OD
ASGTCK1L 40M7 SGC 7D7 LF LC	40-M7	40	7 x Q4 / Q8 / QG (male)	7x Φ6 to Φ8







ASGTCK1L, RECEPTACLE, TERMINATION WITH THREAD
FOR M40 ADAPTER



Part number	Insert arrangement	Shell size	Q-contact
ASGTCK1L 40M7 SGC M40 LC	40-M7	40	7 x Q4 / Q8/QG (male)

Q-CONTACT

Contact	Drawing	Contact number	Part number	Extraction tool
Q4-Contact 		4 x #16 Socket	ASGTC MQ416 SC LC	ASGTC-R-Q
		4 x #16 Pin	ASGTC FQ416 PC LC	ASGTC-R-Q
Q8-Contact 		8 x #20 Socket	ASGTC MQ 820 SC LC	ASGTC-R-Q
		8 x #20 Pin	ASGTC FQ 820 PC LC	ASGTC-R-Q
Q4S-Contact 		4 x #20 Pin	ASGTC FQS 420 SC LC	ASGTC-R-QS
		4 x #20 Socket	ASGTC MQS 420 PC LC	ASGTC-R-QS
QG-Contact 		8 x #22 Pin	ASGTC MQ 822 SC	ASGTC-R-Q
		8 x #22 Socket	ASGTC FQ 822 SC	ASGTC-R-Q

PIN & SOCKET

Contact	Part number		Wire size	Plating	Tools	
	Pin	Socket			Crimping	Extraction
#16 contact for Q4 	ASRC16PC001AU	ASRC16SC001AU	0.6 to 1.5 mm ²	Gold	M22520/1-01	ASGTC-R-16S
	ASRC16PC002AU	ASRC16SC002AU	0.3 to 0.6 mm ²	Gold	M22520/1-01	ASGTC-R-16S
#20 contact for Q8 	C42000409801	C42000409901	22 to 26 AWG	Gold	M22520/2-01	M81969/1-02
	C42000409804	C42000409904	20 AWG	Gold	M22520/2-01	M81969/1-02
#20 contact for Q4S 	C420004821	C420004820	0.3 to 0.6 mm ²	Gold	M22520/2-01	M81969/1-02
#22 contact for QG 	C42000409806	C42000409906	0.13 to 0.32 mm ²	Gold	M22520/2-01	—

Q-contact Extraction tool ASGTC-R-Q	QS Extraction tool ASGTC-R-QS
	
#16 Extraction tool ASGTC-R-16S	#20 Extraction tool M81969/1-02
	
#16 Crimping tool M22520/1-01	#20 / #22 Crimping tool M22520/2-01
	

HVGTC HIGH VOLTAGE REVERSE BAYONET CONNECTOR



HVGTC Environmental cylindrical reverse coupling connector with self-locking system, which guarantee a fast locking and unlocking. Designed for rail and mass transit, high range of current up to 700A and 3000V max high voltage.



KEY FEATURES

High voltage up to 3000V

High current up to 700A

Crimp contacts

Resistant to vibrations and shocks

Various of insert arrangement available

Sealing, IP67

MECHANICAL	
Durability	≥ 500 mating cycles
Vibration & shock	According to TB2761-1996 / IEC 61373-1999 (GB/T 21563-2008) Category 2
ELECTRICAL	
Rated current	100A to 1000A
Rated voltage	1000V to 4000V
Dielectric withstand voltage	2Ui+2000V (1 min.)
Insulator resistance	≥ 5000MΩ (DC500V)
Temperature rise	≤ 60K
ENVIRONMENTAL	
Temperature range	-55°C to 125°C
Humidity	90% to 95% (40±2°C)
Sealing	IP67 (DIN EN 60529)
Salt spray	96h (zinc)
Flammability	EN45545
MATERIAL	
Shell	Alu.alloy, black anodized or green plating
Inserts	Thermoplastic
Contact	Copper alloy, gold or silver plating
Sealing gasket	Silicon rubber

	HVGTC	6	L	20	01	S	C	D	/	X
HVGTC: With self-locking system										
HVGTCN: Without self-locking system										
Connector type:										
0: Cable mounted receptacle (Circular flange)										
1: Cable mounted receptacle (Square flange)										
2: Wall or box mounted receptacle (Circular flange)										
3: Wall or box mounted receptacle (Square flange)										
5: Jam nut receptacle										
6: Straight plug										
8: R/A plug										
Service class:										
L: Water proof										
A: Non-watertight										
Shell size:										
20, 32, 36, 48										
Insert arrangement:										
Please refer to below										
Contact type:										
P: Pin										
S: Socket										
Contact wire type:										
C: Crimp										
M: Screw										
Backshell type:										
A: Cable clamp without sleeve										
D: Nut										
LF: With hoop										
Cable entry size (ΦA):										
(Backshell type A,D) 35: 35mm ² Cable size										
Shell plating:										
Omit: Olive drab zinc										
B: Black Anodized										
G: Green plating										
N: Nickel										
Other request, please contact us.										

HVGT 1 PIN

HVGT 2001 500V



Insert arrangement: 20-01

Contact size: 10mm Radsok / Crimp type

Max rated current: 250A



Max rated voltage: 500V r.m.s

HVGT6L-2001-D, STRAIGHT PLUG, NUT TERMINATION (FEMALE CONTACT)





Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGT6L 2001 SC D22	20-01	20	10mm	22mm ²	ASGTC-R-R10S	$\phi 8.0$ to $\phi 10.0$
HVGT6L 2001 SC D50	20-01	20	10mm	50mm ²	ASGTC-R-R10S	$\phi 14.5$ to $\phi 16.0$

HVGT6L-2001-A, STRAIGHT PLUG, WITH CABLE CLAMP, TRACTION RESISTANT (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGT6L 2001 SC A22	20-01	20	10mm	22mm ²	ASGTC-R-R10S	$\phi 7.5$ to $\phi 9.5$
HVGT6L 2001 SC A50	20-01	20	10mm	50mm ²	ASGTC-R-R10S	$\phi 10.5$ to $\phi 12.5$

HVGT1L-2001-D, RECEPTACLE, NUT TERMINATION (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGT1L 2001 PC D22	20-01	20	10mm	22mm ²	ASGTC-R-R10S	$\phi 8.0$ to $\phi 10.0$
HVGT1L 2001 PC D50	20-01	20	10mm	50mm ²	ASGTC-R-R10S	$\phi 14.5$ to $\phi 16.0$

HVGTC 3201 3000V


Insert arrangement: 32-01
 Contact size: 18mm Radsok
 Max rated current: 700A (18mm Radsok)
 Max rated voltage: 3000V r.m.s

HVGTC6L 3201 PC AXXX, STRAIGHT PLUG, WITH CABLE CLAMP (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC6L 3201 PC AXX	32-01	32	18mm	50 to 240 mm ²	ASGTC-R-R18	Φ18 to Φ32

HVGTC6L 3201 PC DXXX, STRAIGHT PLUG, NUT TERMINATION (MALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC6L 3201 PC DXX	32-01	32	18mm	50 to 240 mm ²	ASGTC-R-R18	Φ18 to Φ32

HVGTC1L 3201 SC AXXX, RECEPTACLE, WITH CABLE CLAMP (FEMALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC1L 3201 SC AXX	32-01	32	18mm	50 to 240 mm ²	ASGTC-R-R18	Φ18 to Φ32

HVGT 1 PIN


HVGT 3201 3000V

HVGT1L 3201 SC DXXX, RECEPTACLE, NUT TERMINATION (FEMALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGT1L 3201 SC DXX	32-01	32	18mm	50 to 240 mm ²	ASGTC-R-R18	$\phi 18$ to $\phi 32$

HVGT3A 3201 SC XXX, BOX MOUNTED RECEPTACLE (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Cable OD
HVGT3A 3201 SC R18 XXX	32-01	32	18mm	50 to 185 mm ²	$\phi 14.5$ to $\phi 16.0$

HVGT5A 3201 SM XXX, JAM NUT RECEPTACLE




Part number	Insert arrangement	Shell size	Contact size
HVGT5A 3201 SM XXX	32-01	32	18mm

HVGTC 3601 3000V


Insert arrangement: 36-01
 Contact size: 23mm Crimp type
 Max rated current: 1000A
 Max rated voltage: 3000V r.m.s
 Cable size: 50mm² to 240mm²

HVGTC6L 3601 PC AXX STRAIGHT PLUG, WITH 2PCS CABLE CLAMP (MALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC6L 3601 PC AXXX	36-03	36	23 mm	50 to 240 mm ²	HVGTC-R-R23	Φ18 to Φ32

HVGTC1L 3601 SC AXXX RECEPTACLE, WITH 2PCS CABLE CLAMP (FEMALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC1L 3601 SC AXXX	36-01	36	23 mm	50 to 240 mm ²	HVGTC-R-R23	Φ18 to Φ32

HVGC 3 PIN

HVGC 3603 2000V


Insert arrangement: 36-03
 Contact size: 6mm Crimp type
 Max rated current: 100A
 Max rated voltage: 2000V r.m.s
 Cable size: 14mm² to 25mm²

HVGC6L 3603 SC DXX, PLUG, WITH CABLE CLAMP (FEMALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGC6L 3603 SC DXX	36-03	36	3 x R6	14 to 25 mm ²	ASGTC-R-R6	Φ8 to Φ10

HVGC1L 3603 PC DXX, CABLE MOUNTED RECEPTACLE (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGC1L 3603 PC DXX	36-03	36	3 x R6	14 to 25 mm ²	ASGTC-R-R6	Φ8 to Φ10

HVGTC6L 3603 SC LF XX, STRAIGHT PLUG WITH HOOP TERMINATION (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC6L 3603 SC LF XX	36-03	36	3 x R6	14 to 25 mm ²	ASGTC-R-R6	Φ8 to Φ10

HVGTC3A 3603 PC XX, BOX MOUNTED RECEPTACLE (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC3A 3603 PC XX	36-03	36	3 x R6	14 to 25 mm ²	ASGTC-R-R6	Φ8 to Φ10

HVGTC 3 PIN

HVGTC 3603 2000V


Insert arrangement: 36-03
Contact size: 8mm Crimp type
Max rated current: 150A
Max rated voltage: 2000V r.m.s
Cable size: 14mm² to 50mm²

HVGTC6L 3603 SC MXX, PLUG WITH THREAD AND PG ADAPTER TERMINATION (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC6L 3603 SC MXX	36-03	36	3 x R8	14 to 50 mm ²	ASGTC-R-R8	Φ8 to Φ14

HVGTC3A 3603 PC XX MOUNTED RECEPTACLE (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTC3A 3603 PC XX	36-03	36	3 x R8	14 to 50 mm ²	ASGTC-R-R8	Φ8 to Φ14

HVGTCN 4003 2500V


Insert arrangement: 40-03
 Contact size: 10mm Radsok / Crimp
 Max rated current: 250A
 Max rated voltage: 2500V r.m.s
 Cable size: 25mm² to 70mm²

HVGTCN6L 4003 SC AXX, STRAIGHT PLUG, WITH CABLE CLAMP (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTCN6L 4003 SC AXX	40-03	40	3 x R10	25 to 70 mm ²	ASGTC-R-R10	Φ14 to Φ18

HVGTCN3L 4003 PC AXX, RECEPTACLE WITH CABLE CLAMP (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTCN3L 4003 PC AXX	40-03	40	3 x R10	25 to 70 mm ²	ASGTC-R-R10	Φ14 to Φ18

HVGTCN 4 PIN

HVGTCN 4004 2000V


Insert arrangement: 40-04
Contact size: 6mm Crimp
Max rated current: 100A
Max rated voltage: 2000V r.m.s
Cable size: 14mm² to 25mm²

HVGTCN6L 4004 SC AXX, STRAIGHT PLUG, WITH CABLE CLAMP (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTCN6L 4004 SC AXX	40-04	40	4 x R6	14 to 25 mm ²	ASGTC-R-R6	Φ8 to Φ10

HVGTCN3A 4004 PC R6 XX, BOX MOUNTED RECEPTACLE (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTCN3A 4004 PC AXX	40-04	40	4 x R6	14 to 25 mm ²	ASGTC-R-R6	Φ8 to Φ10

HVGTC 4803 3000V

Insert arrangement: 48-03
Contact size: 10mm Crimp
Max rated current: 250A
Max rated voltage: 3000V r.m.s
Cable size: 25mm² to 70mm²


Insert arrangement: 48-03
Contact size: 14mm Crimp
Max rated current: 250A
Max rated voltage: 3000V r.m.s
Cable size: 25mm² to 95mm²

HVGTC6L 4803 SC DXX, STRAIGHT PLUG, WITH CABLE CLAMP (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Spanner for cable clamp	Spanner for coupling	Cable OD
HVGTC6L 4803 SC DXX	48-03	48	3 x R10	25 to 70 mm ²	ASGTC-R-R10	ASGTC-B48A	ASGTC-B48B	Φ14 to Φ18
HVGTC6L 4803 SC DXX	48-03	48	3 x R14	25 to 95 mm ²	ASGTC-R-R10	ASGTC-B48A	ASGTC-B48B	Φ14 to Φ18

HVGTC3L 4803 PC DXX, RECEPTACLE WITH CABLE CLAMP (MALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Spanner for cable clamp	Spanner for coupling	Cable OD
HVGTC3L 4803 PC DXX	48-03	48	3 x R10	25 to 70mm ²	ASGTC-R-R10	ASGTC-B48A	ASGTC-B48B	Φ14 to Φ18
HVGTC3L 4803 PC DXX	48-03	48	3 x R14	25 to 95mm ²	ASGTC-R-R10	ASGTC-B48A	ASGTC-B48B	Φ14 to Φ18

HVGTG 4 PIN



HVGTG 4804 3000V

Insert arrangement: 48-04
Contact size: 10mm Crimp
Max rated current: 250A
Max rated voltage: 3000V r.m.s
Cable size: 25mm² to 70mm²

HVGTG 4804 500V



Insert arrangement: 48-04
Contact size: 14mm Crimp
Max rated current: 350A
Max rated voltage: 500V r.m.s
Cable size: 25mm² to 95mm²

HVGTG6L 4804 SC DXX B, STRAIGHT PLUG, WITH CABLE CLAMP (FEMALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTG6L 4804 SC D25 B	48-04	48	10mm	25mm ²	ASGTC-R-R10	Φ12.0 to Φ14.0
HVGTG6L 4804 SC D35 B	48-04	48	10mm	35mm ²	ASGTC-R-R10	Φ13.0 to Φ15.0
HVGTG6L 4804 SC D50 B	48-04	48	10mm	50mm ²	ASGTC-R-R10	Φ14.0 to Φ16.0
HVGTG6L 4804 SC D70 B	48-04	48	10mm	70mm ²	ASGTC-R-R10	Φ16.0 to Φ18.0
HVGTG6L 4804 SC D95 B	48-04	48	14mm	95mm ²	EMP3-3 RR14	Φ19.5 to Φ21.5

HVGTG3A 4804 PC XX B, BOX MOUNTED RECEPTACLE (MALE CONTACT)



Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool	Cable OD
HVGTG3A 4804 PC 25 B	48-04	48	10mm	25mm ²	ASGTC-R-R10	Φ12.0 to Φ14.0
HVGTG3A 4804 PC 35 B	48-04	48	10mm	35mm ²	ASGTC-R-R10	Φ13.0 to Φ15.0
HVGTG3A 4804 PC 50 B	48-04	48	10mm	50mm ²	ASGTC-R-R10	Φ14.0 to Φ16.0
HVGTG3A 4804 PC 70 B	48-04	48	10mm	70mm ²	ASGTC-R-R10	Φ16.0 to Φ18.0
HVGTG3A 4804 PC 95 B	48-04	48	14mm	95mm ²	EMP3-3 RR14	Φ19.5 to Φ21.5

HVGTC 4806 2000V

Insert arrangement: 48-06

Contact size: 14mm / 2.4mm Crimp



Max rated current: 350A (Power) / 23A (Signal)

Max rated voltage: 2000V r.m.s (Power) / 500V r.m.s (Signal)

Cable size: 25mm² to 95mm² (Power)



1.0mm² to 4.0mm² (Signal)

HVGTC6L 4806 SC R14, STRAIGHT PLUG, NUT TERMINATION (FEMALE CONTACT)





Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool
HVGTC6L 4806 SC R14 25	48-06	48	14mm	25mm ²	EMP33-R-R14
			2.4mm	1.0 to 4.0 mm ²	ASGTC-R-12
HVGTC6L 4806 SC R14 XX	48-06	48	14mm	35 to 95 mm ²	EMP33-R-R14
			2.4mm	1.0 to 4.0 mm ²	ASGTC-R-12

HVGTC1L 4806 PC R14, BOX MOUNTED RECEPTACLE (MALE CONTACT)




Part number	Insert arrangement	Shell size	Contact size	Crimping cable	Extraction tool
HVGTC1L 4806 PC R14 25	48-06	48	14mm	25mm ²	EMP33-R-R14
			2.4mm	1.0 to 4.0 mm ²	ASGTC-R-12
HVGTC1L 4806 PC R14 XX	48-06	48	14mm	35 to 95 mm ²	EMP33-R-R14
			2.4mm	1.0 to 4.0 mm ²	ASGTC-R-12

PANEL MOUNTED DIMENSIONS



Front mounted



Rear mounted


Dimension: mm

Shell size	$\phi A(\pm_0^1)$	$B \pm 0.2$	$\phi C \pm 0.2$
	Front / Rear Mounted		
20	36	33	5.5
32	54	46	5.5
36	59.5	52	5.5
40	73.5	62	6.5
48	93.5	90	8.5

Remark: Panel thickness below 5mm for rear mounted and must use with nut.

TOOLS

No.	Crimping tool		Cable size
1	APHWA23KIT		14 to 50 mm ²
2	APH96-978-2		25 & 50 mm ²
3	Crimping tool APSM240-10		10 to 240 mm ²
4	Crimping tool MS400-10 match with Hydraulic pump CP700		16 to 400 mm ²

#R6 Extraction tool ASGTC-R-R6	#R10 Extraction tool ASGTC-R-R8	#R10 Extraction tool ASGTC-R-R10	#R14 Extraction tool EMP 33-R-R14
			
#R16, R18 Extraction tool ASGTC-R-R16	#R23 Extraction tool HVGTC-R-R23	Spanner for cable clamp Fo shell size 48 ASGTC-B48A	Spanner for coupling For shell size 48 ASGTC-B48B
			
Crimping tool APHWA23KIT (Pneumatic)	Crimping tool APH96-978-2 (Hydraulic pressure)	Crimping tool APMS240-10 (Hydraulic pressure)	Crimping tool APMS240-10 (Electric)
			

Amphenol PCD Shenzhen

Building 21
1st Liao Keng Industrial Zone
Shi Yan Street, Bao An District Shenzhen 518108
China

Tel.: +86 755-8173-8000
Fax: +86 755-8173-8180
Email: inquiry@amphenolpcd.com.cn

www.amphenolpcd.com.cn

Notes:

Amphenol PCD Shenzhen has made every effort to ensure that the information contained in this catalog is accurate at the time of publication. Specifications or information stated in this publication are subject to change without notice.

Amphenol PCD Shenzhen reserves the right to clarify this catalog.