

HIGHLY RUGGED TRANSMIT & RECEIVE

FIBER OPTIC MEDIA CONVERTERS



These new media converters have been tested through Apache gunfire vibration and designed in on some of the most rugged airborne applications on earth.



Stand Alone Six Channel Fiber Optic Media Converter
Part Number: CF-020011-40X

- Converts Six channels of fiber optics at up to 1.6Gbps data rates to high speed copper using Amphenol Octonet contacts
- Fiber inputs are 850nm multimode optics but can be configured for single mode
- Input power is brought in over separate MIL-DTL-38999 and is compatible with a wide range of DC voltages
- -40C to +85C operating temperatures and meant for the most rugged of aerospace applications
- Vibration tested through Apache gunfire
- LED indicators show when optical signals are present on the receivers
- Flexible to support additional channels if needed
- Weight: 0.63lbs





Stand Alone Single Channel Fiber Optic Media Converter
Part Number: CF-020011-35X




- Converts one channel of copper high speed signalling at up to 1.6Gbps data rates to high speed fiber optics using Amphenol M29504 contacts
- Fiber outputs are 850nm multimode optics but can be configured for single mode
- Input power is brought in over a copper cable and is compatible with a wide range of DC voltages
- -40C to +85C operating temperatures and meant for the most rugged of aerospace applications
- Vibration tested through Apache gunfire
- Flexible to support additional channels if needed
- Weight: 0.35lbs (without cable)
- Available unterminated or terminated with 10-628485-185N or others

STAND ALONE SIX CHANNEL FIBER OPTIC MEDIA CONVERTER

CF-020011-40X




LOS - Loss of Signal






STAND ALONE SINGLE CHANNEL FIBER OPTIC MEDIA CONVERTER

CF-020011-35X





FRONT ISOMETRIC VIEW

REAR ISOMETRIC VIEW




Pair 1 - 100 Ω Differential Pair for Data

Pair 2 - 24 AWG for Power




BLOCK DIAGRAMS

CF-020011-35X



CF-020011-40X



System View

