

Bundle Solutions for 5G

Low PIM - TFT 5G-401

- Ultraflexible bundled harness
- -160 dBc for optimal system performance
- Rugged fire retardant polyurethane jacket

Specifications

Ω Impedance
50 Ohms

Op Temp
-67 to 221°F
-55 to 105°C

	Diameter	Minimum Bend Radius	Weight	Shielding
Number of Cables	in (mm)	in (mm)	lb/1000ft (kg/1000m)	dB
4	0.760 (19.3)	7.6 (193.04)	367 (166.46)	-80
5	0.265 (6.68)	8.2 (208.28)	455 (206.38)	-80



Number of Cables	450	600	900	1900	2100	2500	3500	4900	5800
	dB/100ft (dB/100m)								
4	5.4 (17.8)	6.4 (21.1)	8.2 (26.9)	13.1 (42.9)	14.0 (45.8)	15.6 (51.2)	19.5 (64.0)	24.5 (80.3)	27.5 (90.2)
5	5.4 (17.8)	6.4 (21.1)	8.2 (26.9)	13.1 (42.9)	14.0 (45.8)	15.6 (51.2)	19.5 (64.0)	24.5 (80.3)	27.5 (90.2)

Ordering Guide

TMQ	N	TFT401	XX.X	Y	W
	N-4 = MQ4 N-5 = MQ5		Length / 3 dig	F Feet M Meters	Boot